



### 9M

#### Maschio Male Connector




Raccordo disponibile anche con tenuta elastomerica ISO 1179-2.  
Per ordinare: sostituire nel codice il prefisso 9M con **9ME**.

Straight fitting available also with elastomeric sealing ISO 1179-2.  
To order: substitute the code prefix 9M with **9ME**.

Codice Code	∅ est. tubo Tube O.D.	F (ORFS)	F4 (BSPP)	Ch5	H3	L8	P2	T
9M-06-1/8	6	9/16"-18	1/8"	16	8	25	1,2	10
9M-06-1/4	6	9/16"-18	1/4"	19	12	30,5	1,8	10
9M-06-3/8	6	9/16"-18	3/8"	24	12	30,5	1,8	10
9M-10-1/4	8-10	11/16"-16	1/4"	19	12	31,5	1,8	11
9M-10-3/8	8-10	11/16"-16	3/8"	24	12	31,5	1,8	11
9M-10-1/2	8-10	11/16"-16	1/2"	27	14	35	1,8	11
9M-12-1/4	12	13/16"-16	1/4"	22	12	36	1,8	13
9M-12-3/8	12	13/16"-16	3/8"	24	12	33,5	1,8	13
9M-12-1/2	12	13/16"-16	1/2"	27	14	37	1,8	13
9M-12-3/4	12	13/16"-16	3/4"	36	16	41	1,8	13
9M-16-3/8	14÷16	1"-14	3/8"	27	12	41,5	1,8	15,5
9M-16-1/2	14÷16	1"-14	1/2"	27	14	39,5	1,8	15,5
9M-16-3/4	14÷16	1"-14	3/4"	36	16	43,5	1,8	15,5
9M-20-1/2	18-20	1.3/16"-12	1/2"	32	14	46,5	1,8	17
9M-20-3/4	18-20	1.3/16"-12	3/4"	36	16	45	1,8	17
9M-20-1	18-20	1.3/16"-12	1"	41	18	47,5	2,5	17
9M-25-3/4	25	1.7/16"-12	3/4"	38	16	50	1,8	17,5
9M-25-1	25	1.7/16"-12	1"	41	18	48	2,5	17,5
9M-25-1.1/4	25	1.7/16"-12	1.1/4"	50	20	51,5	2,5	17,5
9M-32-1	30-32	1.11/16"-12	1"	46	18	54,5	2,5	17,5
9M-32-1.1/4	30-32	1.11/16"-12	1.1/4"	50	20	51,5	2,5	17,5
9M-38-1.1/2	38	2"-12	1.1/2"	60	22	55,5	2,5	17,5

### 9TOL

#### "T" Orientabile in Linea Adjustable Branch Tee



Codice Code	∅ est. tubo Tube O.D.	F (ORFS)	F4 (BSPP)	Ch1	Ch9	H	H3	L	P2
9TOL-06-1/8	6	9/16"-18	1/8"	14	14	29,5	8	21,5	1,2
9TOL-06-1/4	6	9/16"-18	1/4"	19	19	36	12	23,5	1,8
9TOL-06-3/8	6	9/16"-18	3/8"	19	24	38,5	12	25	1,8
9TOL-10-1/4	8-10	11/16"-16	1/4"	19	19	36	12	25	1,8
9TOL-10-3/8	8-10	11/16"-16	3/8"	19	24	38,5	12	26,5	1,8
9TOL-10-1/2	8-10	11/16"-16	1/2"	27	27	48,5	14	29,5	1,8
9TOL-12-1/4	12	13/16"-16	1/4"	19	19	36	12	28	1,8
9TOL-12-3/8	12	13/16"-16	3/8"	19	24	38,5	12	28	1,8
9TOL-12-1/2	12	13/16"-16	1/2"	27	27	48,5	14	31	1,8
9TOL-12-3/4	12	13/16"-16	3/4"	30	36	51,5	16	33,5	1,8
9TOL-16-3/8	14÷16	1"-14	3/8"	27	24	44	12	33,5	1,8
9TOL-16-1/2	14÷16	1"-14	1/2"	27	27	48,5	14	33,5	1,8
9TOL-16-3/4	14÷16	1"-14	3/4"	30	36	51,5	16	36	1,8
9TOL-20-1/2	18-20	1.3/16"-12	1/2"	30	27	49,5	14	37,5	1,8
9TOL-20-3/4	18-20	1.3/16"-12	3/4"	30	36	51,5	16	37,5	1,8
9TOL-20-1	18-20	1.3/16"-12	1"	37	41	58,5	18	41	2,5
9TOL-25-3/4	25	1.7/16"-12	3/4"	37	36	58	16	41,5	1,8
9TOL-25-1	25	1.7/16"-12	1"	37	41	58,5	18	41,5	2,5
9TOL-25-1.1/4	25	1.7/16"-12	1.1/4"	41	50	61	20	44,5	2,5
9TOL-32-1	30-32	1.11/16"-12	1"	41	41	61	18	44,5	2,5
9TOL-32-1.1/4	30-32	1.11/16"-12	1.1/4"	41	50	61	20	44,5	2,5
9TOL-38-1.1/2	38	2"-12	1.1/2"	48	60	64,5	22	49	2,5