

SPM type

Pulsation and noise damper with tubular

Technical data

Operating pressure:

SPM 10>40 max 250/330 bar

Gas filling (nitrogen only): max. 90% of min. operating pressure

Admissible pressure ratio: -

Operating temperature: -40 +150°C (Compatible with the temperatures admitted for the diaphragms)

Mounting: horizontal or vertical with gas valve upwards

Standard construction characteristics

Material of body:

SPM 10>40 carbon steel, stainless steel AISI 316L

Bladder: according to fluid


Gas connection valve: 5/8"UNF version 1

Painting: anti-rust primer (only carbon steel)

Test: on request

3

SPM 10>40



Tipo	Volume nominale cm ³	Pressione			Attacco lato liquido E	Portata max pompa lit/min	Pressione azoto max bar	Dimensioni			Peso kg
		max bar	Stainless steel	Carbon steel				Duplex steel	mm ØD	L1	
SPM 10	80.00	250	330	-	1/2"G	40	-	-	-	0.00	
SPM 15	400.00	250	330	-	1"G	150	-	-	-	0.00	
SPM 25	1000.00	250	330	-	1"G	150	-	-	-	0.00	
SPM 40	1500.00	250	330	-	1"1/2G	200	-	-	-	0.00	