



fig. 1

G	PN	SW	h	fig.	sealing	part number (NBR)
M8x1	250	17	38	1	o-ring type 1	1-G06-20-21-600-CF
M10x1	630	17	38	1	o-ring type 1	1-G06-22-21-600-CF
M10x1	400	17	39	1	soft sealing type 3	1-G06-22-11-600-CF
M10x1,25		17	38	1	o-ring type 1	1-G06-49-21-600-CF
M10x1,25		17	38	1	soft sealing type 3	1-G06-49-11-600-CF
M12x1,5	630	17	39	1	soft sealing type 3	1-G06-23-11-600-CF
M14x1,5	630	19	37	1	soft sealing type 3	1-G06-24-11-600-CF
M14x1,5	630	19	38	1	o-ring type 5	1-G06-24-61-600-CF
M16x1,5	630	22	37	1	soft sealing type 3	1-G06-25-11-600-CF
M18x1,5		24	39	1	soft sealing type 3	1-G06-26-11-600-CF
M20x1,5		27	39	1	soft sealing type 3	1-G06-51-11-600-CF
M22x1,5		27	39	1	soft sealing type 3	1-G06-27-11-600-CF
G 1/8	400	17	39	1	soft sealing type 3	1-G06-28-11-600-CF
G 1/4	630	19	37	1	soft sealing type 3	1-G06-29-11-600-CF
G 3/8	630	22	37	1	soft sealing type 3	1-G06-30-11-600-CF
G 1/2	630	27	39	1	soft sealing type 3	1-G06-31-11-600-CF
5/16-24 UNF	400	17	38	1	o-ring type 5	1-G06-38-30-600-CF
7/16-20 UNF	630	17	38	1	o-ring type 5	1-G06-39-30-600-CF
1/2-20 UNF	630	17	38	1	o-ring type 5	1-G06-61-30-600-CF
9/16-18 UNF	630	19	38	1	o-ring type 5	1-G06-40-30-600-CF
3/4-16 UNF	630	27	40	1	o-ring type 5	1-G06-41-30-600-CF

For metal cap type A (universal) with vibration security replace 600 by

590

 For metal cap type B (round) **without vibration security** replace 600 by

020

 For metal cap type A (universal) **without vibration security** replace 600 by

010

 For yellow plastic cap type A (universal) **without vibration security** replace 600 by

100