

Indicators



VACUUM GAUGE

| NBR | FKM | Vacuum gauge | NBR | FKM | Vacuum gauge |
|-----|-----|---------------------------|-----|-----|---------------------------|
| 10 | - | Scale 0 ÷ 100 kPa (1 bar) | 11 | - | Scale 0 ÷ 100 kPa (1 bar) |
| | | | | | |





PRESSURE GAUGE

| NBR | FKM | Pressure gauge | | | |
|-----|-----|----------------------------|--|--|--|
| 30 | - | Scale 0 ÷ 600 kPa (6 bar) | | | |
| NBR | FKM | Pressure gauge | | | |
| 31 | - | Scale 0 ÷ 1,2 MPa (12 bar) | | | |
| NBR | FKM | Pressure gauge | | | |
| 32 | - | Scale 0 ÷ 600 kPa (6 bar) | | | |
| 33 | - | Scale 0 ÷ 1,2 MPa (12 bar) | | | |





DIFFERENTIAL INDICATORS



| NBR | FKM | Differential VISUAL indicator | NBR | FKM | Differential ELECTRICAL indicator |
|-----|-----|------------------------------------|---|-----|-----------------------------------|
| U0 | W0 | Setting 130 kPa (1,3 bar) | N0 | S0 | Setting 130 kPa (1,3 bar) |
| | | | | | |
| | | | <p>SPDT differential switch. C.C. 14 - 30 V: > max resistive or inductive load 4 - 3 A respectively C.A. 125-250 V: > max resistive or inductive load 1 A Protection IP65 Connector DIN 43650</p> | | |
| NBR | FKM | Differential VISUAL indicators | | | |
| 5B | AB | Setting 130 kPa (1,3 bar) | | | |
| 5C | AC | Setting 200 kPa (2 bar) | | | |
| 5D | AD | Setting 250 kPa (2,5 bar) | | | |
| 5E | AE | Setting 500 kPa (5 bar) | | | |
| 5F | AF | Setting 800 kPa (8 bar) | | | |
| NBR | FKM | Differential ELECTRICAL indicators | | | |
| 6B | CB | Setting 130 kPa (1,3 bar) | | | |
| 6C | CC | Setting 200 kPa (2 bar) | | | |
| 6D | CD | Setting 250 kPa (2,5 bar) | | | |
| 6E | CE | Setting 500 kPa (5 bar) | | | |
| 6F | CF | Setting 800 kPa (8 bar) | | | |
| | | | <p>SPDT differential switch. C.C. 14 - 30 V: > max resistive or inductive load 4 - 3 A respectively C.A. 125-250 V: > max resistive or inductive load 1 A Protection IP65 Connector DIN 43650</p> | | |



VACUUM SWITCH



| NBR | FKM | Vacuum switch | | |
|-----|-----|---------------------------|--|---|
| 91 | - | Setting 20 kPa (0,2 bar) |  | ATEX 3 GD EEx e T6  |
| | | | | SPDT. C.C. 30V: > max resistive or inductive load 3A - 1A respectively C.A. 125 or 250V: > max resistive or inductive load 3A - 0,5A respectively Protection IP65 Connector DIN 43650 |
| S8 | - | Setting 25 kPa (0,25 bar) |  |  |



PRESSURE SWITCH

| NBR | FKM | Pressure switch | | |
|-----|-----|---------------------------|---|---|
| P4 | - | Setting 130 kPa (1,3 bar) |  | ATEX 3 GD EEx e T6  |
| P1 | - | Setting 150 kPa (1,5 bar) | | |
| P6 | - | Setting 200 kPa (2 bar) | | |
| R8 | - | Setting 150 kPa (1,5 bar) |  |  |

| NBR | FKM | Differential ELECTRICAL indicators with LED (24V) for visual indication | | |
|-----|-----|---|--|--|
| 7B | EB | Setting 130 kPa (1,3 bar) |  | Recommended tightening torque 90 Nm  |
| 7C | EC | Setting 200 kPa (2 bar) | | |
| 7D | ED | Setting 250 kPa (2,5 bar) | | |
| 7E | EE | Setting 500 kPa (5 bar) | | |
| 7F | EF | Setting 800 kPa (8 bar) | | |

| NBR | FKM | Differential ELECTRICAL indicators with THERMOSTAT 30°C | | |
|-----|-----|---|--|--|
| T0 | DB | Setting 130 kPa (1,3 bar) |  | Recommended tightening torque 90 Nm  |
| T1 | DC | Setting 200 kPa (2 bar) | | |
| T6 | DD | Setting 250 kPa (2,5 bar) | | |
| T2 | DE | Setting 500 kPa (5 bar) | | |
| T3 | DF | Setting 800 kPa (8 bar) | | |

| NBR | FKM | Differential VISUAL ELECTRICAL indicators | | |
|-----|-----|---|--|--|
| 70 | E0 | Setting 130 kPa (1,3 bar) |  | Recommended tightening torque 90 Nm  |
| 71 | E1 | Setting 200 kPa (2 bar) | | |
| 76 | E6 | Setting 250 kPa (2,5 bar) | | |
| 72 | E2 | Setting 500 kPa (5 bar) | | |
| 73 | E3 | Setting 800 kPa (8 bar) | | |

| NBR | FKM | Differential ELECTRICAL indicator | | |
|-----|-----|-----------------------------------|--|---|
| X6 | - | Setting 250 kPa (2,5 bar) |  |  |
| | | | | N.O. differential switch. C.C. 28-48V: > max resistive or inductive load 5 - 3A respectively C.A. 125-250 V: > max resistive or inductive load 4A Protection IP65-IP69K Connector AMP timer |