

HOSE

ISOBARIC SPIRAL

C6000D

ULTRA FLEXIBLE
EXTRA ABRASION RESISTANT
FRAS
ISOBARIC SPIRAL HOSE
420 BAR / 6100 PSI
MILLION CYCLE



RECOMMENDED FOR:

Ultra flexibility and small bend radius provides easy installation in compact environments.
Extremely high pressure hydraulic oil lines.
Constant pressure (Isobaric) 420 bar / 6100 psi in all sizes.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of:
ISO 18752-CC, SAE 100R15.

TUBE:

Black, oil resistant synthetic rubber.

REINFORCEMENT:

Four alternating layers of spiralled high tensile steel wire.

COVER:

DIEHARD™ Black, oil and extra abrasion resistant synthetic rubber. Flame Resistant, Anti-Static (FRAS) & MSHA compliant. Highly visible layline branding for easy and permanent identification. No skiving required with T7000 Series Crimp Couplings.

FEATURES:

Ultra flexibility combined with a small bend radius reduces effort during assembly and installations. Tested to **1 million impulse cycles** at up to 1/2 SAE 100R15 Minimum Bend Radius. Constant pressure 420 bar / 6100 psi in all sizes for easy system design and hose selection.

FRAS - FLAME RESISTANCE AND ANTI-STATIC:

DIEHARD™ complies with Flame Resistant and Electrical Resistance (Anti-Static) requirements of Australian Standard AS 2660 and Methods of Test AS 1180.10B and 13A. Meets Flame Resistant Designation "U.S. MSHA" of the US Department of Labor, Mine Safety and Health Administration.

TEMPERATURE RANGE:

-40°C to +121°C (-40°F to +250°F).

WORKING PRESSURE:

Maximum working pressures are based on 4:1 safety factor (maximum working pressure to minimum burst pressure).

COUPLINGS:

NON-SKIVE ONE-PIECE CRIMP

T7000 Series (sizes -12 to -16) pages 272 to 302.
Assembly Instructions pages 478.

C6000D - DIEHARD ULTRA FLEXIBLE ISOBARIC SPIRAL HOSE		NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES	
PART NO	HOSE SIZE	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	ONE PIECE	
C6012D	19 -12	19,1	3/4	28,5	1.12	420	6100	1680	24400	115	4.5	1,15	0.77	NON-SKIVE T7000	
C6016D	25 -16	25,4	1	35,8	1.41	420	6100	1680	24400	165	6.5	1,75	1.17	NON-SKIVE T7000	

Refer to the latest RYCO Crimp Charts for crimp diameter and mark lengths.