



PETROFOR SD /10 R4

TUBO ASPIRAZIONE E MANDATA OLI IDRAULICI | HYDRAULIC OIL SUCTION AND DELIVERY HOSE
TUYAU ASPIRATION ET REFOULEMENT DES HUILES HYDRAULIQUES | SAUG- UND DRUCKSCHLAUCH FÜR HYDRAULIKÖL



APPLICAZIONE Aspirazione e mandata di oli idraulici	APPLICATION Suction and delivery hose for hydraulic oils	APPLICATION Tuyau aspiration et refoulement des huiles hydrauliques	ANWENDUNG Saug- und Druckschlauch für Hydrauliksysteme
SOTTOSTRATO Nero, liscio in gomma sintetica	TUBE Black, smooth synthetic rubber compound	TUBE INTERIEUR Noir, lisse en caoutchouc synthétique	INNENSEELE Schwarz, glatt, synthetischer Gummi
RINFORZO Tessuti sintetici ad alta tenacità, con spirali metalliche incorporate	REINFORCEMENT High strength synthetic plies with steel wire spirals	ARMATURE Nappes synthétiques très résistantes avec spirales métalliques	EINLAGEN Hochreißfestes synthetisches Cordgewebe mit eingearbeiteter Stahldrahtspirale
COPERTURA Nera, liscia ad impressione tela, in gomma sintetica , resistente agli oli, all'ozono ed agli agenti atmosferici	COVER Black, smooth, cloth impression synthetic rubber compound, resistant to oils, ozone and weathering	REVETEMENT EXTERIEUR Caoutchouc synthétique noir, lisse, grain toile, résistant à l'huile, à l'ozone et aux agents atmosphériques	DECKE Schwarz, stoffgemustert, synthetischer Gummi, beständig gegen Öl, Ozon- und witterungsbeständig
TEMPERATURA D'ESERCIZIO -40°C +100°C	WORKING TEMPERATURE -40°F +212°F	TEMPERATURE -40°C +100°C	BETRIEBSTEMPERATUR -40°C +100°C

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
13	1/2	23	29/32	0,43	10	150	30	450	78	0,9	40
16	5/8	26	1 1/32	0,55	10	150	30	450	96	0,9	40
19	3/4	29	1 9/64	0,67	10	150	30	450	110	0,9	40/61
25	1	35	1 3/8	0,77	10	150	30	450	140	0,9	40/61
30	1 3/16	40	1 37/64	0,91	10	150	30	450	170	0,9	40/61
32	1 1/4	42	1 21/32	0,97	10	150	30	450	190	0,9	40/61
35	1 3/8	45	1 25/32	1,08	10	150	30	450	210	0,9	40/61
38	1 1/2	48	1 57/64	1,20	10	150	30	450	230	0,9	40/61
40	1 37/64	50	1 31/32	1,28	10	150	30	450	240	0,9	40/61
42	1 21/32	52	2 3/64	1,35	10	150	30	450	250	0,9	40/61
45	1 25/32	56	2 13/64	1,49	10	150	30	450	260	0,9	40/61
51	2	62	2 7/16	1,76	10	150	30	450	280	0,9	40/61
60	2 23/64	72	2 53/64	2,10	10	150	30	450	340	0,9	40/61
63,5	2 1/2	75	2 61/64	2,37	10	150	30	450	340	0,9	40/61
70	2 3/4	82	3 15/64	2,62	10	150	30	450	410	0,7	40/61
76	3	88	3 15/32	2,80	10	150	30	450	430	0,7	40/61
80	3 5/32	94	3 45/64	3,15	10	150	30	450	460	0,7	40/61
90	3 35/64	103	4 1/16	3,47	10	150	30	450	520	0,7	40/61
102	4	115	4 17/32	4,00	10	150	30	450	590	0,7	40/61
110	4 21/64	126	4 61/64	4,65	10	150	30	450	660	0,7	40/61
127	5	144	5 43/64	5,36	10	150	30	450	792	0,7	40/61
152	6	170	6 11/16	8,00	10	150	30	450	912	0,7	40/61
203	8	223	8 25/32	11,40	10	150	30	450	1230	0,7	40/61

Identificazione / Branding / Marquage / Kennzeichnung



PETROFOR

SD W.P. 10 BAR

ITALY



tubi gomma torino

TGT PETROFOR

SD W.P. 10 BAR

ITALY

tubi gomma torino