

Male stud branch tees

BSP taper
DIN 3852-2 form C



	PN	ØD	C	Body only	Single-bite ring	Double-bite ring	Bell code	F1*	F2	L1	L2	L3	kg
LL	100	4	R1/8	8008E04 10	8108E04 10		15-03/LL4RK	9	10	21	11	17	0,032
		6	R1/8	8008E06 10	8108E06 10		15-03/LL6RK	9	12	21	9,5	17	0,034
		8	R1/8	8008E08 10	8108E08 10		15-03/LL8RK	12	14	23	11,5	20	0,044
L	315	6	R1/8	8008L06 10		8208L06 10	ZS15-03/L6RK	12	14	27	12	20	0,059
		8	R1/4	8008L08 13		8208L08 13	ZS15-03/L8RK	14	17	29	14	26	0,087
		10	R1/4	8008L10 13		8208L10 13	ZS15-03/L10RK	17	19	30	15	27	0,119
		12	R3/8	8008L12 17		8208L12 17	ZS15-03/L12RK	19	22	32	17	28	0,156
		15	R1/2	8008L15 21		8208L15 21	ZS15-03/L15RK	19	27	36	21	34	0,215
		18	R1/2	8008L18 21		8208L18 21	ZS15-03/L18RK	24	32	40	23,5	36	0,304
S	400	6	R1/4	8008S06 13		8208S06 13	ZS15-03/S6RK	14	17	31	16	26	0,106
		8	R1/4	8008S08 13		8208S08 13	ZS15-03/S8RK	17	19	32	17	27	0,135
		10	R3/8	8008S10 17		8208S10 17	ZS15-03/S10RK	19	22	34	17,5	28	0,186
		12	R3/8	8008S12 17		8208S12 17	ZS15-03/S12RK	22	24	38	21,5	28	0,236
		14	R1/2	8008S14 21		8208S14 21	ZS15-03/S14RK	19	27	40	22	32	0,242
		16	R1/2	8008S16 21		8208S16 21	ZS15-03/S16RK	24	30	43	24,5	32	0,309

* Models ØD 4 to 10mm are manufactured from profile steel
Models ØD > 10mm are manufactured from forged steel.