


Adjustable male stud branch tees (DKO)

24° sealing cone and O-ring



	PN	ØD	C	Body only	Double-bite ring	DiNova ring	Bell code	F1*	F2	L1	L2	L3	O-ring	kg	
L	400	6	M12x1,5	8074L06 00	8274L06 00	8374L06 00	ZS14/2-29/L6V-DM	12	14	27	12	26	4x1,5	0,065	
		8	M14x1,5	8074L08 00	8274L08 00	8374L08 00	ZS14/2-29/L8V-DM	14	17	29	14	27,5	6x1,5	0,077	
		10	M16x1,5	8074L10 00	8274L10 00	8374L10 00	ZS14/2-29/L10V-DM	17	19	30	15	29	7,5x1,5	0,100	
		12	M18x1,5	8074L12 00	8274L12 00	8374L12 00	ZS14/2-29/L12V-DM	19	22	32	17	29,5	9x1,5	0,132	
		15	M22x1,5	8074L15 00	8274L15 00	8374L15 00	ZS14/2-29/L15V-DM	19	27	36	21	32,5	12x2	0,226	
	315	18	M26x1,5	8074L18 00	8274L18 00	8374L18 00	ZS14/2-29/L18V-DM	24	32	40	23,5	35,5	15x2	0,337	
		22	M30x2	8074L22 00	8274L22 00	8374L22 00	ZS14/2-29/L22V-DM	27	36	44	27,5	38,5	20x2	0,436	
		28	M36x2	8074L28 00	8274L28 00	8374L28 00	ZS14/2-29/L28V-DM	36	41	47	30,5	41,5	26x2	0,616	
		250	35	M45x2	8074L35 00	8274L35 00	8374L35 00	ZS14/2-29/L35V-DM	41	50	56	34,5	51	32x2,5	0,918
		42	M52x2	8074L42 00	8274L42 00	8374L42 00	ZS14/2-29/L42V-DM	50	60	63	40	56	38x2,5	1,063	
S	630	6	M14x1,5	8074S06 00	8274S06 00	8374S06 00	ZS14/2-29/S6V-DM	14	17	31	16	27	4x1,5	0,097	
		8	M16x1,5	8074S08 00	8274S08 00	8374S08 00	ZS14/2-29/S8V-DM	17	19	32	17	27,5	6x1,5	0,118	
		10	M18x1,5	8074S10 00	8274S10 00	8374S10 00	ZS14/2-29/S10V-DM	19	22	34	17,5	30	7,5x1,5	0,157	
		12	M20x1,5	8074S12 00	8274S12 00	8374S12 00	ZS14/2-29/S12V-DM	22	24	38	21,5	31	9x1,5	0,214	
		14	M22x1,5	8074S14 00	8274S14 00	8374S14 00	ZS14/2-29/S14V-DM	19	27	40	22	35	10x2	0,280	
	400	16	M24x1,5	8074S16 00	8274S16 00	8374S16 00	ZS14/2-29/S16V-DM	24	30	43	24,5	36,5	12x2	0,367	
		20	M30x2	8074S20 00	8274S20 00	8374S20 00	ZS14/2-29/S20V-DM	27	36	48	26,5	44,5	16,3x2,4	0,601	
		25	M36x2	8074S25 00	8274S25 00	8374S25 00	ZS14/2-29/S25V-DM	36	46	54	30	50	20,3x2,4	1,028	
		30	M42x2	8074S30 00	8274S30 00	8374S30 00	ZS14/2-29/S30V-DM	41	50	62	35,5	55	25,3x2,4	1,338	
		315	38	M52x2	8074S38 00	8274S38 00	8374S38 00	ZS14/2-29/S38V-DM	50	60	72	41	63	33,3x2,4	1,988

* Models ØD 6 to 10mm are manufactured from profile steel
Models ØD > 10mm are manufactured from forged steel

Discover it on legris.com

- A dynamic catalogue of the complete range - to **consult** and, through which, to request a **quotation**.
- A technical guide with **animated presentations** of product ranges.
- More than 3000 CAD drawings available.

