



BSP FITTINGS 60°
INSERTI BSP 60°

C45G

DKR 45° - BSP FEMALE 45°, 60° CONE
DKR 45° - FEMMINA 45° BSP, CONO 60°

Thread - *Filetto*: BSP

Norme - *Norma*: BS 5200

Notes

CRIMPED NUT

Note

DADO PINZATO

| Code Article <i>Codice Articolo</i> | Thread <i>Filetto</i> | Hose <i>Tubo</i> | | Dimensions (mm) <i>Dimensioni (mm)</i> | | |
|--|--------------------------|---------------------|---------|---|-----|----|
| | | Inch/Pollici | DN (mm) | CH | A | B |
| | F | | | | | |
| C45G0203 | 1/8-28 | 3/16 | 5 | 15 | 38 | 13 |
| C45G0204 | 1/8-28 | 1/4 | 6 | 15 | 38 | 13 |
| C45G0403 | 1/4-19 | 3/16 | 5 | 19 | 40 | 16 |
| C45G0404 | 1/4-19 | 1/4 | 6 | 19 | 41 | 16 |
| C45G0405 | 1/4-19 | 5/16 | 8 | 19 | 53 | 17 |
| C45G0406 | 1/4-19 | 3/8 | 10 | 19 | 55 | 17 |
| C45G0604 | 3/8-19 | 1/4 | 6 | 22 | 43 | 18 |
| C45G0605 | 3/8-19 | 5/16 | 8 | 22 | 54 | 18 |
| C45G0606 | 3/8-19 | 3/8 | 10 | 22 | 57 | 18 |
| C45G0608 | 3/8-19 | 1/2 | 12 | 22 | 62 | 19 |
| C45G0806 | 1/2-14 | 3/8 | 10 | 27 | 60 | 21 |
| C45G0808 | 1/2-14 | 1/2 | 12 | 27 | 65 | 22 |
| C45G1008 | 5/8-14 | 1/2 | 12 | 30 | 68 | 25 |
| C45G1010 | 5/8-14 | 5/8 | 16 | 30 | 77 | 25 |
| C45G1208 | 3/4-14 | 1/2 | 12 | 32 | 69 | 26 |
| C45G1210 | 3/4-14 | 5/8 | 16 | 32 | 79 | 27 |
| C45G1212 | 3/4-14 | 3/4 | 19 | 32 | 82 | 26 |
| C45G1612 | 1"-11 | 3/4 | 19 | 38 | 84 | 28 |
| C45G1616 | 1"-11 | 1" | 25 | 38 | 111 | 31 |