



METRIC FITTINGS 24°  
INSERTI METRICI 24°

## C45ES

DKOS 45° - METRIC O-RING FEMALE 45°, 24° CONE, HEAVY  
DKOS 45° - FEMMINA 45° METRICA O-RING, CONO 24°, SERIE PESANTE

Thread - *Filetto*: METRIC  
Norme - *Norma*: DIN 3865

### Notes

- \* CRIMPED NUT
- \*\* WHILE STOCKS LAST

### Note

- \* DADO PINZATO
- \*\* ARTICOLO IN ESAURIMENTO

Code Article <i>Codice Articolo</i>	Thread <i>Filetto</i>	Hose <i>Tubo</i>	Standpipe <i>Codolo</i>	Dimensions (mm) <i>Dimensioni (mm)</i>			
	F	Inch/Pollici	DN (mm)	mm	CH	A	B
C45ES0603	M14X1,5	3/16	5	6	17	36	15
C45ES0604*	M14X1,5	1/4	6	6	17	47	22
C45ES0803	M16x1,5	3/16	5	8	19	38	18
C45ES0804	M16x1,5	1/4	6	8	19	50	16
C45ES1004	M18x1,5	1/4	6	10	22	51	18
C45ES1005	M18x1,5	5/16	8	10	22	56	17
C45ES1006*	M18x1,5	3/8	10	10	22	63	25
C45ES1204	M20x1,5	1/4	6	12	24	53	17
C45ES1205	M20x1,5	5/16	8	12	24	56	17
C45ES1206	M20x1,5	3/8	10	12	24	58	18
C45ES1406	M22x1,5	3/8	10	14	27	59	20
C45ES1608	M24x1,5	1/2	12	16	30	64	22
C45ES2010	M30x2	5/8	16	20	36	77	26
C45ES2012	M30x2	3/4	19	20	36	82	25
C45ES2512	M36x2	3/4	19	25	46	84	28
C45ES2516	M36x2	1"	25	25	46	110	31
C45ES3016	M42x2	1"	25	30	50	115	35
C45ES3020**	M42x2	1"1/4	32	30	50	145	37
C45ES3820	M52x2	1"1/4	32	38	60	146	38