


## DKL METRIC (LIGHT) 24° CONE



HOSE SIZE		THRD SIZE	TUBE SIZE	DASH SIZE	MALE HEX		DKL MALE 24° CONE				
DN	inch	mm	mm		HM-SPANNER		PART NO	C <sub>A</sub>		L	
					inch	mm		inch	mm	inch	mm
6	1/4	12x1,5	6	-0412		14	<b>T2650-0412</b>	1.06	27	2.09	53
6	1/4	14x1,5	8	-0414		17	<b>T2650-0414</b>	1.06	27	2.09	53
6	1/4	16x1,5	10	-0416		17	<b>T2650-0416</b>	1.14	29	2.13	54
6	1/4	18x1,5	12	-0418	3/4	19	<b>T2650-0418</b>	1.18	30	2.17	55
8	5/16	16x1,5	10	-0516		17	<b>T2650-0516</b>	1.14	29	2.13	54
8	5/16	18x1,5	12	-0518	3/4	19	<b>T2650-0518</b>	1.18	30	2.17	55
10	3/8	16x1,5	10	-0616		17	<b>T2650-0616</b>	1.22	31	2.20	56
10	3/8	18x1,5	12	-0618	3/4	19	<b>T2650-0618</b>	1.26	32	2.24	57
10	3/8	22x1,5	15	-0622	15/16	24	<b>T2650-0622</b>	1.38	35	2.36	60
12	1/2	18x1,5	12	-0818	3/4	19	<b>T2650-0818</b>	1.34	34	2.32	59
12	1/2	22x1,5	15	-0822	7/8	22	<b>T2650-0822</b>	1.38	35	2.36	60
12	1/2	26x1,5	18	-0826	1.3/16	30	<b>T2650-0826</b>	1.42	36	2.40	61
16	5/8	26x1,5	18	-1026	1.3/16	30	<b>T2650-1026</b>	1.34	34	2.52	64
16	5/8	30x2,0	22	-1030	1.1/4	32	<b>T2650-1030</b>	1.50	38	2.68	68
19	3/4	26x1,5	18	-1226	1.3/16	30	<b>T2650-1226</b>	1.50	38	2.64	67
19	3/4	30x2,0	22	-1230	1.1/4	32	<b>T2650-1230</b>	1.65	42	2.80	71
25	1	36x2,0	28	-1636	1.5/8	41	<b>T2650-1636</b>	1.73	44	2.95	75
31	1.1/4	45x2,0	35	-2045		46	<b>T2650-2045</b>	2.01	51	3.94	100
38	1.1/2	52x2,0	42	-2452	2.3/16	55	<b>T2650-2452</b>	1.89	48	3.90	99