



Rubrik 2.23

Light Series - Metric - 24°-Cone



For Compression Couplings DIN 2353 / DIN EN ISO 8434-1 with 24°-Cone Light Series = CEL

Hose	Bore	Thread	Tube O.D.	Approx. Dimensions			Order-Code
DN	in.	G	D	A	C	SW	
05	3/16"	M 12 x 1,5	6	21,5	3,0	14	CEL-06-DN 05
06	1/4"	M 12 x 1,5	6	23,0	4,0	14	CEL-06-DN 06
05	3/16"	M 14 x 1,5	8	21,5	3,0	14	CEL-08-DN 05
06	1/4"	M 14 x 1,5	8	23,0	4,0	14	CEL-08-DN 06
06	1/4"	M 16 x 1,5	10	25,0	4,0	17	CEL-10-DN 06
08	5/16"	M 16 x 1,5	10	24,5	5,5	17	CEL-10-DN 08
10	3/8"	M 16 x 1,5	10	24,5	7,0	17	CEL-10-DN 10
06	1/4"	M 18 x 1,5	12	24,5	4,0	19	CEL-12-DN 06
08	5/16"	M 18 x 1,5	12	24,5	5,5	19	CEL-12-DN 08
10	3/8"	M 18 x 1,5	12	24,5	7,0	19	CEL-12-DN 10
12	1/2"	M 18 x 1,5	12	25,5	9,5	19	CEL-12-DN 12
10	3/8"	M 22 x 1,5	15	26,0	7,0	22	CEL-15-DN 10
12	1/2"	M 22 x 1,5	15	27,0	9,5	22	CEL-15-DN 12
12	1/2"	M 26 x 1,5	18	29,0	9,5	27	CEL-18-DN 12
16	5/8"	M 26 x 1,5	18	28,0	12,5	27	CEL-18-DN 16
19	3/4"	M 26 x 1,5	18	30,0	14,5	27	CEL-18-DN 19
16	5/8"	M 30 x 2	22	32,5	12,5	30	CEL-22-DN 16
19	3/4"	M 30 x 2	22	35,0	14,5	30	CEL-22-DN 19
25	1"	M 30 x 2	22	32,0	20,0	32	CEL-22-DN 25
19	3/4"	M 36 x 2	28	34,0	19,5	36	CEL-28-DN 19



25	1"	M 36 x 2	28	35,0	20,0	36	CEL-28-DN 25
31	1 1/4"	M 45 x 2	35	39,0	25,5	46	CEL-35-DN 31
38	1 1/2"	M 52 x 2	42	45,0	31,5	55	CEL-42-DN 38
51	2"	M 52 x 2	42	49	35,0	60	CEL-42-DN 51