



FERULES FOR TEXTILE PROTECTION  
BOCCOLE FERMA GUAINA

## BG

SLEEVE FOR TEXTILE PROTECTION  
BOCCOLA PER GUAINA TESSILE

Notes

MATERIAL:  
STEEL  
SURFACE TREATMENT:  
Cr3 GALVANIZATION  
THE FERRULE IS USED TO STOP THE TEXTILE  
PROTECTION (CODE "GTN") IN THE RIGHT  
POSITION AFTER THE ASSEMBLING ON THE  
FLEXIBLE HOSES. IT MUST BE CRIMPED IN  
CORRESPONDANCE OF THE FERRULE  
CRIMPED ON THE RUBBER HOSE IN ORDER  
TO STOP THE SLIDE OF THE PROTECTION.

| Code Article<br>Codice Articolo | Dimensions (mm)<br>Dimensioni (mm) |    |           |            |            |            |           |     |
|---------------------------------|------------------------------------|----|-----------|------------|------------|------------|-----------|-----|
|                                 | D1                                 | L  | 15NK      | 25NK       | 15N        | 25N        | 4SP       | 4SH |
| BG03                            | 19                                 | 30 | 1/4       | -          | -          | -          | -         | -   |
| BG04                            | 22                                 | 30 | 5/16      | 1/4 - 5/16 | 1/4 - 5/16 | 1/4        | -         | -   |
| BG06                            | 27                                 | 30 | 3/8       | 3/8 - 1/2  | 3/8 - 1/2  | 5/16 - 3/8 | -         | -   |
| BG0810                          | 32                                 | 30 | 1/2 - 5/8 | 5/8        | 5/8        | 1/2        | 1/2       | -   |
| BG12                            | 38                                 | 35 | 3/4       | 3/4        | 3/4        | 5/8 - 3/4  | 5/8 - 3/4 | 3/4 |
| BG16                            | 46                                 | 50 | 1"        | 1"         | 1"         | 1"         | 1"        | 1"  |

Note

MATERIALE: ACCIAIO  
TRATTAMENTO SUPERFICIALE:  
ZINCATURA Cr3  
LA BOCCOLA VIENE UTILIZZATA PER  
FERMARE LE ESTREMITA' DELLA GUAINA  
TESSILE, (CODE "GTN") NELLA CORRETTA  
POSIZIONE DOPO IL MONTAGGIO SUI TUBI  
FLESSIBILI.