

LIFTING CUSHIONS

LIFTING CUSHIONS

AA

6-65 Tn.

8 bar

TOOLS



LARZEP advantages

- Pneumatic cushion made of friction resistant material.
- Collapsed height of 28 mm.
- Working pressure: 8 bar.
- 1/4" BSP male thread.
- Excellent for lifting loads at restricted spaces.
- Used in rescue operations, rubble lifting in collapses and other lifting applications with very limited access.
- Use two cushions to increase the lifting height.
- Hoses, couplers and control valves are available.

Model	Valve	Weight
LARZEP	Outlet No.	kg
AZN6100	1	1,1
AZN6501	2	2,2

Model	Hose
LARZEP	m
AZN2020	2
AZN2040	4
AZN2100	10

Model	Coupler
LARZEP	1/4" BSP
AZN3021	Male
AZN3041	Female

Model	Max. Capacity*	Stroke	Volume	Dimensions	Weight
LARZEP	Tn	mm	l	mm	kg
AA00617	6	175	4,5	300x300x28	2,5
AA01423	14	235	11,7	420x420x28	6
AA01928	19	280	23,4	510x510x28	8
AA03034	30	345	41,4	620x620x28	12
AA04341	43	410	72,0	750x750x28	17
AA06550	65	500	139,5	920x920x28	23

* Maximum capacity when using the maximum effective lifting area.