
HYDRAULIC POWERPACKS (SOLENOID VALVE)



LARZEP advantages

- Remote pendant controlled solenoid valves with up, down and emergency stop button.
- Internal safety valve set at 700 bar to prevent overpressure.
- External adjustable pressure relief valve.
- For use with single acting or double acting cylinders for heavy lifting or production applications.
- Supplied with a 3 metre cable with remote pendant.
- Options: roll bars, oil cooler, pressure transducer, wheel kit and pedal. See page 92.

Larzep designs and manufactures powerpacks upon request according to ATEX standards.



Capacity	A	B	C
l	mm	mm	mm
2,5	220	160	400
5	280	200	481
8,5-10	340	247	525
12,5-14	368	290	548
25	450	325	667
50	540	415	752
100	830	500	837



Synchronized Lifting Systems, HAS.
Page. 94

HYDRAULIC POWERPACKS

HAE

2,5-100 litres

700 bar

50-60 Hz 3 phase								
Tank	Flow at 700 bar	Flow at 60 bar	230 V		400/415 V		Power	Weight
l	l/min	l/min	Single/A	Double/A	Single/A	Double/A	kW	kg
2,5	0,36	-	HAE1162	HAE1172	HAE1164	HAE1174	0,56	22
5	0,51	-	HAE2262	HAE2272	HAE2264	HAE2274	0,75	27
5	0,36	4	HAE7262	HAE7272	HAE7264	HAE7274	0,75	27
8,5	0,70	-	HAE3362	HAE3372	HAE3364	HAE3374	1,00	40
8,5	1,17	-	HAE4362	HAE4372	HAE4364	HAE4374	1,50	40
10	0,36	4	HAE7362	HAE7372	HAE7364	HAE7374	0,75	32
12,5	1,17	-	HAE4462	HAE4472	HAE4464	HAE4474	1,50	52
14	0,36	4	HAE7462	HAE7472	HAE7464	HAE7474	0,75	37
25	2,20	-	HAE5562	HAE5572	HAE5564	HAE5574	3,00	79
25	2,20	11*	HAE8562	HAE8572	HAE8564	HAE8574	4,00	89
50	2,20	11*	HAE8662	HAE8672	HAE8664	HAE8674	4,00	131
50	4,00	25*	HAE9662	HAE9672	HAE9664	HAE9674	5,50	159
100	4,00	25*	HAE9762	HAE9772	HAE9764	HAE9774	5,50	243

* Flow at 100 bar

50 Hz Single Phase								
Tank	Flow at 700 bar	Flow at 60 bar	115 V		230 V		Power	Weight
l	l/min	l/min	Single/A	Double/A	Single/A	Double/A	kW	kg
5	0,36	-	HAE1265	HAE1275	HAE1261	HAE1271	0,75	32
5	0,51	-	HAE2265	HAE2275	HAE2261	HAE2271	0,75	35
5	0,36	4	HAE7265	HAE7275	HAE7261	HAE7271	0,75	35
10	0,36	4	HAE7365	HAE7375	HAE7361	HAE7371	0,75	40
12,5	1,17	-	HAE4465	HAE4475	HAE4461	HAE4471	2,20	63
14	0,36	4	HAE7465	HAE7475	HAE7461	HAE7471	0,75	45

60 Hz Single Phase								
Tank	Flow at 700 bar	Flow at 60 bar	115 V		230 V		Power	Weight
l	l/min	l/min	Single/A	Double/A	Single/A	Double/A	kW	kg
5	0,36	-	HAE1266	HAE1276	HAE1263	HAE1273	0,75	32
5	0,51	-	HAE2266	HAE2276	HAE2263	HAE2273	0,75	35
5	0,36	4	HAE7266	HAE7276	HAE7263	HAE7273	0,75	35
10	0,36	4	HAE7366	HAE7376	HAE7363	HAE7373	0,75	40
12,5	1,17	-	HAE4466	HAE4476	HAE4463	HAE4443	2,20	63
14	0,36	4	HAE7466	HAE7476	HAE7463	HAE7473	0,75	45