

TORQUE WRENCH PUMPS



LARZEP advantages

- Tanks from 5 to 14 litres.
- Push button controlled solenoid valves.
- Internal safety valve set at 700 bar to prevent overpressure.
- Precision adjustable pressure regulating valve.
- 4 ways / 2 positions valve.
- For use with double acting torque wrenches only.
- Supplied with a 3 metre cable with remote pendant.
- Easy to operate: Pressing the button advances the tool and when releasing it retracts automatically.
- Option: Oil cooler. Add 'H' to the reference.

Tank	Flow at 700 bar	Flow at 60 bar	Valve	50 Hz Single Phase		60Hz Single Phase		Power	Weight
	l/min	l/min		230 V	115 V	230 V	115 V		
5	0,36	4	4/2	HAT7291	HAT7295	HAT7293	HAT7296	0,75	34,4
10	0,36	4	4/2	HAT7391	HAT7395	HAT7393	HAT7396	0,75	40,6
14	0,36	4	4/2	HAT7491	HAT7495	HAT7493	HAT7496	0,75	44,4

Tank	Flow at 700 bar	Flow at 60 bar	Valve	50/60 Hz 3 Phase		Power	Weight
	l/min	l/min		230 V	400 V		
5	0,36	4	4/2	HAT7292	HAT7294	0,75	31,4
10	0,36	4	4/2	HAT7392	HAT7394	0,75	37,6
14	0,36	4	4/2	HAT7492	HAT7494	0,75	41,4

TORQUE WRENCH PUMPS



HAT

5-14 litres

700 bar

PUMPS

Capacity	A	B	C
l	mm	mm	mm
5	460	280	540
10	500	350	600
14	540	368	615

