



The **SPRADOW TEST BOX** is a solid, oil resistant plastic box. It is available either pre-assembled with an assortment of our most popular components or equipped to your specific needs. The pressure gauges, the gauge adapters and the hose are safely nestled in a Plastazote® cushion. Plastazote® is an oil-repellent cross-linked polyethylene foam, which has been especially chosen for this range of application.

The test couplings and reducers of the instant pressure checking equipment are safely and clearly arranged in separate arrays beneath the transparent cover, which can be securely locked. Further arrays are available for your individual requirements.

standard equipment:		STB20FBV-E2-xxx/xxx-CF
pcs	description	
1	Test hose 2000 mm length, M16x2 / M16x2	1-971-04-04-110-CF
1	Pressure gauge Ø 63 mm / G 1/4	1-982-01-01- <u>xxx</u>
1	Pressure gauge Ø 63 mm / G 1/4	1-982-01-01- <u>xxx</u>
1	Pressure gauge connector G 1/4	1-918-29-01-240-CF
1	Direct pressure gauge connector G 1/4	1-927-29-01-020-CF
1	Test coupling G 1/4	1-906-29-11-600-CF
1	Test coupling M 10 x 1	1-906-22-21-600-CF
1	Reducer G 3/8	4-924-03-01-260-CF
1	Reducer G 1/2	4-924-03-01-760-CF

pressure gauge	
order no.	bar
-040	6
-050	10
-060	16
-070	25
-080	40
-090	60
-100	100
-110	160
-120	250
-130	400
-140	600

The content of the SPADOW TEST BOX are adaptable to your specifications.

ORDER EXAMPLE: SPRADOW TEST BOX with 1 pressure gauge 100 bar and 1 pressure gauge 400 bar: **STB20FBV-E2-100/130-CF**



The **SPRADOW TEST BOX** is a solid, oil resistant plastic box. It is available either pre-assembled with an assortment of our most popular components or equipped to your specific needs. The pressure gauges, the gauge adapters and the hose are safely nestled in a Plastazote® cushion. Plastazote® is an oil-repellent cross-linked polyethylene foam, which has been especially chosen for this range of application.

The test couplings and reducers of the instant pressure checking equipment are safely and clearly arranged in separate arrays beneath the transparent cover, which can be securely locked. Further arrays are available for your individual requirements.

standard equipment:		STB20FBV-S6-001-CF (without pressure gauges)
pcs.	description	
1	Test hose 2000 mm length, M16x2 / M16x2	1-971-04-04-110-CF
1	Pressure gauge connector G 1/4	1-918-29-01-240-CF
1	Direct pressure gauge connector G 1/4	1-927-29-01-020-CF
1	Test coupling G 1/4	1-906-29-11-600-CF
1	Test coupling M 10 x 1	1-906-22-21-600-CF
1	Reducer G 3/8	4-924-03-01-260-CF
1	Reducer G 1/2	4-924-03-01-760-CF
up to 6	Pressure gauges to your specifications	1-982-01-01-xxx

pressure gauge	
order no.	bar
-040	6
-050	10
-060	16
-070	25
-080	40
-090	60
-100	100
-110	160
-120	250
-130	400
-140	600

The content of the SPADOW TEST BOX are adaptable to your specifications.

The SPRADOW TEST BOX is also available for the series M16x2-piston (STB20KFBV-...), M16x1,5-ball (STB15FBV-...), M16x1,5-piston (STB15KFBV-...), S12x1,5 (STB12KFBV-...) and series Steck (STBSTECK-...).