


ADATTATORI GIREVOLI JIC-GAS CILINDRICO JIC-BSPP SWIVEL NUTS ADAPTERS




COG

Curva Orientabile con Girevole
Adjustable elbow with Swivel Nut




Codice Code	∅ est. tubo Tube O.D.	JIC	F4 (BSPP)	Ch1	Ch2	Ch9	H	H3	L11	M	P2
COG-06-1/8	6	7/16"-20	1/8"	12	16	14	26	8	26,5	18	1,2
COG-06-1/4	6	7/16"-20	1/4"	14	16	19	31,5	12	26,5	18	1,8
COG-08-1/4	8	1/2"-20	1/4"	14	17	19	31,5	12	27,5	18,5	1,8
COG-10-1/4	10	9/16"-18	1/4"	14	19	19	31,5	12	32	22,5	1,8
COG-12-3/8	12	3/4"-16	3/8"	19	22	24	36,5	12	35,5	25	1,8
COG-16-1/2	14÷16	7/8"-14	1/2"	22	27	27	43	14	41	28,5	1,8
COG-20-3/4	18-20	1.1/16"-12	3/4"	27	32	36	49	16	44,5	30,5	1,8
COG-25-1	25	1.5/16"-12	1"	33	41	41	52	18	51	36	2,5
COG-30-1.1/4	30-32	1.5/8"-12	1.1/4"	41	50	50	57	20	58,5	42,8	2,5
COG-38-1.1/2	38	1.7/8"-12	1.1/2"	48	60	60	61	22	66,5	47,2	2,5





FG

Femmina Girevole
Swivel Nut Female



Codice Code	∅ est. tubo Tube O.D.	JIC	F4 (BSPP)	Ch2	Ch5	H3	K	M2	P2
FG-06-1/8	6	7/16"-20	1/8"	16	16	8	25,5	17	1,2
FG-06-1/4	6	7/16"-20	1/4"	16	19	12	26,5	18,5	1,8
FG-08-1/4	8	1/2"-20	1/4"	17	19	12	28,5	19,5	1,8
FG-08-3/8	8	1/2"-20	3/8"	17	24	12	28,5	19,5	1,8
FG-10-1/4	10	9/16"-18	1/4"	19	19	12	30	20,5	1,8
FG-10-3/8	10	9/16"-18	3/8"	19	24	12	30	20,5	1,8
FG-12-1/4	12	3/4"-16	1/4"	22	19	12	31,5	21	1,8
FG-12-3/8	12	3/4"-16	3/8"	22	24	12	31,5	21	1,8
FG-12-1/2	12	3/4"-16	1/2"	22	27	14	33	22,5	1,8
FG-16-3/8	14÷16	7/8"-14	3/8"	27	24	12	34,5	22	1,8
FG-16-1/2	14÷16	7/8"-14	1/2"	27	27	14	35,5	23	1,8
FG-16-3/4	14÷16	7/8"-14	3/4"	27	36	16	37,5	25	1,8
FG-20-1/2	18-20	1.1/16"-12	1/2"	32	27	14	37	23	1,8
FG-20-3/4	18-20	1.1/16"-12	3/4"	32	36	16	39	25	1,8
FG-20-1	18-20	1.1/16"-12	1"	32	41	18	39,5	25,5	2,5
FG-25-3/4	25	1.5/16"-12	3/4"	41	36	16	41,5	26,5	1,8
FG-25-1	25	1.5/16"-12	1"	41	41	18	42	27	2,5
FG-30-1.1/4	30-32	1.5/8"-12	1.1/4"	50	50	20	46	30,5	2,5
FG-38-1.1/2	38	1.7/8"-12	1.1/2"	60	60	22	54,5	35	2,5



Raccordo disponibile anche con tenuta elastomerica ISO 1179-2.
Per ordinare: sostituire nel codice il prefisso FG con **FGE**.

*Straight fitting available also with elastomeric sealing ISO 1179-2.
To order: substitute the code prefix FG with **FGE**.*