



M2

Maschio


Male Connector



Codice Code	∅ est. tubo Tube O.D.	JIC	F2 (Metric) F2 (Metric)	Ch5	H3	L8	P2	T
M2-06-10	6	7/16"-20	10x1	16	9	30	1	14
M2-06-12	6	7/16"-20	12x1,5	17	11,5	32,5	1,5	14
M2-08-10	8	1/2"-20	10x1	16	9	30	1	14
M2-08-12	8	1/2"-20	12x1,5	17	11,5	32,5	1,5	14
M2-10-14	10	9/16"-18	14x1,5	19	11,5	33,5	1,5	14
M2-10-16	10	9/16"-18	16x1,5	22	12,5	34,5	1,5	14
M2-12-16	12	3/4"-16	16x1,5	22	12,5	37,5	1,5	17
M2-12-18	12	3/4"-16	18x1,5	24	13,5	39,5	1,5	17
M2-16-18	14÷16	7/8"-14	18x1,5	24	13,5	42	1,5	19,5
M2-16-22	14÷16	7/8"-14	22x1,5	30	15	44,5	1,5	19,5
M2-20-22	18-20	1.1/16"-12	22x1,5	30	15	48	1,5	22
M2-20-27	18-20	1.1/16"-12	27x2	36	18,5	52,5	2	22
M2-25-27	25	1.5/16"-12	27x2	36	18,5	53,5	2	23
M2-25-33	25	1.5/16"-12	33x2	41	18,5	54	2	23
M2-30-42	30-32	1.5/8"-12	42x2	50	19,5	58	2	24,5
M2-38-48	38	1.7/8"-12	48x2	60	21,5	65	2	27,5

RACCORDI DISPONIBILI ANCHE SENZA ANELLO DI RITEGNO VERSIONE ISO 6149-1. PER ORDINARE: SOSTITUIRE NEL CODICE IL PREFISSO M2 CON M6.

FITTINGS AVAILABLE ALSO WITHOUT RETAINING-RING ISO 6149-1. TO ORDER: SUBSTITUTE CODE PREFIX M2 WITH M6.




Raccordo disponibile anche con tenuta elastomerica ISO 9974-2. Per ordinare: sostituire nel codice il prefisso M2 con ME2.

Straight fitting available also with elastomeric sealing ISO 9974-2. To order: substitute the code prefix M2 with ME2.

TOL2

"T" Orientabile in Linea

Adjustable Branch Tee



Codice Code	∅ est. tubo Tube O.D.	JIC	F2 (Metric) F2 (Metric)	Ch1	Ch9	H	H3	L	P2
TOL2-06-10	6	7/16"-20	10x1	12	14	27	9	22,5	1
TOL2-06-12	6	7/16"-20	12x1,5	14	17	31,5	11,5	27	1,5
TOL2-08-10	8	1/2"-20	10x1	14	14	27,5	9	24	1
TOL2-08-12	8	1/2"-20	12x1,5	14	17	31,5	11,5	27	1,5
TOL2-10-14	10	9/16"-18	14x1,5	14	19	32	11,5	27	1,5
TOL2-10-16	10	9/16"-18	16x1,5	19	22	38	12,5	28,5	1,5
TOL2-12-16	12	3/4"-16	16x1,5	19	22	38	12,5	31,5	1,5
TOL2-12-18	12	3/4"-16	18x1,5	19	24	39,5	13,5	31,5	1,5
TOL2-16-18	14÷16	7/8"-14	18x1,5	22	24	41	13,5	36,5	1,5
TOL2-16-22	14÷16	7/8"-14	22x1,5	22	27	43	15	36,5	1,5
TOL2-20-22	18-20	1.1/16"-12	22x1,5	27	27	45	15	42	1,5
TOL2-20-27	18-20	1.1/16"-12	27x2	27	36	51,5	18,5	42	2
TOL2-25-27	25	1.5/16"-12	27x2	33	36	52	18,5	46	2
TOL2-25-33	25	1.5/16"-12	33x2	33	41	53	18,5	46	2
TOL2-30-42	30-32	1.5/8"-12	42x2	41	50	58	19,5	52	2
TOL2-38-48	38	1.7/8"-12	48x2	48	60	67	21,5	59	2

RACCORDI DISPONIBILI ANCHE SENZA ANELLO DI RITEGNO VERSIONE ISO 6149-1. PER ORDINARE: SOSTITUIRE NEL CODICE IL PREFISSO TOL2 CON TOL6.

FITTINGS AVAILABLE ALSO WITHOUT RETAINING-RING ISO 6149-1. TO ORDER: SUBSTITUTE CODE PREFIX TOL2 WITH TOL6.